

BIRTUGAN STANDARD EQUIPMENT

Standard equipment

Armature 6"

Rotary lobe pump VOGELSANG 4300 l/min

Automatic switch from collection to mixing

Lever regulating the spreading, hydraulically controlled

Frame adjusted for any type of a dribble bar

Front-rear axle adjustment

Adjustable drawbar

PREMIUM support foot

Dual-circuit air brake system

Control of the tractor hydraulics

Galvanized armature

PTO shaft

Inspection ladder

Brakes (size 520 x 180 mm)

Socket 12V (3-pin)

Slurry tanker structure

Frame 300 x 100 x 8 mm, steel S355J2+N

Tank made of glass fibre with a breakwater

Distance between axles 1820 mm

Clearance 550 mm

Distance piece between the frame and tank, made of polyurethane (prevents the tank abrasion)

European homologation*

**Vehicle approval certificate for movement within the EU, in accordance with current administrative and technical requirements

ALB braking system tested in the field of braking force on the wheels, (dual-circuit air brake system);

Automatic parking brake

LED road lighting+bumper, plates, safety markings for public roads

License plate holder with backlight

Drawbar protection against unwanted connection

* The machine is equipped with the above-mentioned elements, tests are being carried out in order to obtain the Whole Vehicle Approval Certificate for movement within the EU, in accordance with current administrative and technical requirements

** On request