

EM BUFFALO RX HD+ STANDARD EQUIPMENT

Detachable spreader unit type 70

Continuously variable transmission up to max. 250 hp (1000 rot/min) on tractor PTO shaft

Made of quality steel S355J2+N

Reinforced gearbox

Double drum, 2,3 m high*

Weight 1350 kg

Transmission ratio 1/2, 37

Speed of beaters 423 rpm

Beaters \varnothing 324 mm and walls 7,1 mm thick

Replaceable cutting knives HARDOX 12 mm (28 pcs per beater)

Spiral made of 10 mm thick metal sheet

Distance between cutting knives - 40 mm

Bottom plates, diameter 1050 mm, with replaceable paddles

Oil sight glass

Central lubrication of top bearings

Forklift slots

70



Construction of manures spreader

Loading box made of quality steel S355J2+N, 6 mm thick

Double-chain conveyor - \varnothing 18 mm with 33 t breaking capacity per chain

Floor bars with a closed profile

Chain floor conveyor slides

Mechanically adjustable single truck axle (reinforced), cross-section 150 mm, (in models RX 1870 HD+, RX 2070 HD+)

Double turning axle, following with a lock, 2x150 mm (in models RX 2270 HD+, RX 2470 HD+)

Triple turning axle, following with a lock + mudguards, 3x130mm (in model RX 2870 HD+)

Hydraulic continuously variable chain floor conveyor

Air brakes (dual circuit)

Hydraulic support foot

Inspection ladder

Wide-angle PTO shaft

Detachable ball hitch

LED lights

End-outline marker lights

Central deflector for lime seeding

European Homologation

Homologation certificate for movement in the EU, in accordance with the current administrative and technical requirements

The dual-circuit **air braking** system tested in regards to braking force on the wheels; Hand brake

Road safety signs, lights and markings (front, rear, side)

License plate holder (lit)

Protection against unwanted connection (padlock on the hitch)