

## EM BUFFALO RXX HD+ STANDARD EQUIPMENT

### Detachable spreader unit type 90

Continuously variable transmission up to 400 hp (1000 rpm)	90
Made of quality steel S355J2+N	
<b>Reinforced gearbox</b>	
Double-drum, 2 m high*	
Transmission ratio 1/2,36	
Speed of beaters 424 rpm at 1000 rpm of PTO	
Beaters $\varnothing$ 178 mm and 8 mm thick walls	
Replaceable cutting knives HARDOX 12 mm (25 pcs per beater)	
Spiral made of 15 mm thick metal sheet	
Distance between cutting knives - 50 mm	
Bottom plates, diameter 1080 mm, with replaceable paddles	
Oil sight glass	
Central lubrication of top bearings	
<b>Forklift slots</b>	



### Construction of manures spreader

Loading box made of HARDOX steel; 3 mm thick walls and 4 mm thick floor
4-chain conveyor - $\varnothing$ 18 mm with a 33 t breaking capacity per chain
Floor bars with a closed profile
Chain floor conveyor slides
Hydraulic continuously variable chain floor conveyor
Air brakes (dual circuit)
Hydraulic support foot
Inspection ladder
Wide-angle PTO shaft
Detachable ball hitch
LED lights
End-outline marker lights
<b>Central deflector for seeding lime</b>
Road safety signs, lights and markings (front, rear, side)
Two side gearboxes

\* beater height