

FXS HD STANDARD EQUIPMENT

NAME	INFO	
Made of quality steel S355J2+N; reinforced construction, side walls – 8 mm, bottom – 20 mm		
Hydraulic divider (not present with one unloading window) + Manual control (lever + cable)	1 pc	
Auger – 15 mm thick		
Cutting knives	1 set	
Fast planetary gearbox TYPE II + reduction gearbox (2 gears) with gear change extension (slow gear – 17,8 rpm; high gear – 33,5 rpm at the PTO speed of 540 rpm), increases power demand by 30% (in relation to TYPE I)		
Electronic weighing system DG400 with 4 load cells		
One unloading window of choice 1,2 m wide (no 1, 2, 4)		
Window cover		
Discharge chute		
PTO shaft	1 pc	
Manually adjustable two-speed support foot PREMIUM		
Inspection platform with anti-slip cover and folding steps		
Overflow ring welded to the tub		
Height adjustable hitch		
Oil container cover		
Manually adjustable counter-knives		2 pcs
Adaptation for star knives		1 set
Single axle tries 13.0/55-16 (340/55-16)		

It's possible to remove some elements to reduce the price

NAME	AMOUNT TO REDUCE BY (NET IN EURO)
Electronic weighing system DG400	930
PTO shaft	230