

## FX HD STANDARD EQUIPMENT

NAME	INFO
Made of quality steel S355J2+N; reinforced construction, side walls - 8 mm, bottom - 20 mm	
Hydraulic divider (not present with one unloading window) + manual control (lever + cable)	1 pc
Auger - 15 mm thick	
Cutting knives	
Fast planetary gearbox TYPE II + reduction gearbox (2 gears) with gear change extension (low gear - 17,8 rpm; high gear - 33,5 rpm at the PTO speed of 540 rpm), increases the power demand by 30% (in relation to gearbox TYPE I)	
Electronic weighing system DG400 with 4 load cells	
One unloading window of choice 1,2 m wide (no 1, 2, 3, 4, 5, 6, 7, 8, 9)**	
Window cover	
PTO shaft	
Manually adjustable two-speed support foot PREMIUM	
Inspection platform with anti-slip cover and folding steps	
Overflow ring welded to the tub	
Height adjustable hitch	
Oil container cover	
Manually adjustable counter-knives	2 pcs
Adaptation for star knives	1 set
Single axle tyres 13.0/55-16 (340/55-16)	
<b>It's possible to remove some elements to reduce the price</b>	
NAME	AMOUNT TO REDUCE BY (NET IN EURO)
Reduction gearbox (2 gears) with gear change extension*	
Electronic weighing system DG400 with 4 load cells	
PTO shaft	