

FX HD+ STANDARD EQUIPMENT

| NAME | INFO |
|--|-------|
| Made of quality steel S355J2+N, reinforced construction; side walls - 8 mm, bottom - 20 mm | |
| Hydraulic divider (not present with one unloading window) + manual control (lever + cable) | 1 pc |
| Height adjustable hitch | |
| Auger - 20 mm thick | |
| Cutting knives | 1 set |
| Fast planetary gearbox TYPE II + reduction gearbox (2 gears) with gear change extension (low gear - 17,8 rpm; high gear - 33,5 rpm at the speed of PTO 540 rpm), increases the power demand by 30% (in relation to gearbox TYPE I) | |
| Electronic weighing system DG400 with 4 load cells | |
| One unloading window of choice - 1,2 m wide (no 1, 2, 3, 4, 5, 6, 7, 8, 9)** | |
| Window cover | 1 pc |
| PTO shaft | |
| Manually adjustable two-speed support foot PREMIUM | |
| Inspection platform with anti-slip cover and folding steps | |
| Overflow ring screwed-in to the tub on a chain | |
| Oil container cover | |
| Manually adjustable counter-knives | |
| Adaptation for star knives | 1 set |
| Viewing slots on the front of the tub | |
| Single axle tyres R15,5-400/60 | |

It's possible to remove some elements to reduce the price

| NAME | AMOUNT TO REDUCE BY (NET IN EURO) |
|---|-----------------------------------|
| Reduction gearbox (2 gears) with gear change extension* | |
| Electronic weighing system DG400 with 4 load cells | |
| PTO shaft | |