

FXXL HD STANDARD EQUIPMENT	
NAME	INFO
Made of quality steel S355J2+N; reinforced construction, side walls – 8 mm, bottom – 20 mm	
Hydraulic divider (not present with one unloading window) + manual control (lever + cable)	1 pc
Height adjustable hitch	
Overflow ring at 45° angle + overflow ring on a chain	
Augers – 15 mm thick	2 pcs
Cutting knives	1 set
Slow planetary gearbox TYPE I + reduction gearbox (2 gears) (low gear-13,6 rpm; high gear – 25,6 rpm at the PTO speed of 540 rpm)	
Electronic weighing system DG400 with 4 load cells	1 pc
One unloading window of choice 1,0 m wide (FXXL 1200 HD) and 1,2 m (FXXL 1400 HD) (no 1, 2, 3, 4, 5, 6, 7, 8, 9)**	
Window cover	
PTO shaft	
Manually adjustable two-speed support foot PREMIUM	
Inspection platform with anti-slip cover and folding steps	2 pcs
Oil container cover	
Manually adjustable counter-knives	
Adaptation for star knives	1 set
Single axle tyres R15,5-400/60	
It's possible to remove some elements to reduce the price	
Reduction gearbox (2 gears) with a gear change extension*	
Electronic weighing system DG400	
PTO shaft	